




SOM-COM-HPC-A-RPL

COM HPC® Client module Size A, with 13th Gen Intel® Core™ processors (Codename: Raptor Lake – H/P/U series)


13th Gen Core-i processing with AI accelerator for high performance industrial grade edge applications



HIGHLIGHTS

CPU 13th Gen Intel® Core™ processors (Codename: Raptor Lake – H/P/U series)	CONNECTIVITY 2x 2.5GbE; 4x USB4.0 / USB 3.2; 4x USB2.0; 8x PCIe x1 Gen3; 1x PCIe x8 or 2x PCIe x4 Gen4; Optional on-board WiFi 6E + BT 5.2
GRAPHICS Intel® Iris® X® Architecture with up to 96 EUs, up to 4 independent displays	MEMORY Two DDR5 SO-DIMM Slots supporting DDR5-4800 Memory

COM+HPC



MAIN FIELDS OF APPLICATION



Coffee & Vending



Medical



Transportation



Safety & Surveillance



Industrial Automation



Smart Devices



Digital Signage

FEATURES

Processor	13th Gen Intel® Core™ processors, up to 14 cores & up to 20 threads, up to 24MB cache, 15/45W TDP	PCI-e	Up to 8x PCIe x1 Gen3 lanes 1x PCIe x8 Gen4 port 2x PCIe x4 Gen4 ports
Memory	2x DDR5-4800 SODIMM Slots, up to 64GB	Audio	SoundWire and I2S Audio Interface
Graphics	Integrated Iris® X® Architecture, up to 96 Execution Units Up to two video decode boxes (VDBoxes) for enhanced video stream capabilities Support for up to 48 simultaneous 1080p streams ingestion Support for up to four independent displays at up to 4K60 HDR resolution or one display at 8K resolution	Serial Ports	2 x UARTs
Video Interfaces	Up to 3x DDI ports supporting DP 1.4, HDMI 2.0b (HDMI 2.1 via LSPCON) Up to 2x DP++ interfaces over USB 4.0 (Factory alternatives to 2x DDI ports) 1x eDP 1.4b interface	Other Interfaces	2x 4-lane CSI-2 interfaces SPI, SM Bus, 2x I2C, Watchdog timer, Carrier board FAN Control Management signals, ACPI signals, Safety Status signals Deep Sleep / Battery support Optional TPM 2.0 module on-board 12x GPIOs
Video Resolution	DP: Up to 5120x3200 @60Hz 24bpp / 7680x4320@60Hz 30bpp with DSC eDP: Up to 5120x3200 @60Hz 24bpp / 5120x3200@120Hz 30bpp with DSC HDMI® 1.4: Up to 4Kx2K 24-30Hz 24bpp HDMI® 2.1: Up to 4Kx2K 48-60Hz 24bpp / 4Kx2K 48-60Hz 12bpc (need dedicated redriver on carrier board)	Other	AI engine: Intel® Gaussian & Neural Accelerator 3.0 (Intel® GNA) Can operate while the SOC is in lower power states
Mass Storage	2x external SATA Gen3 Channels PCI-e x4 ports can be used to connect, on the carrier board, M.2 NVMe drives	Power Supply	+8V _{DC} - +20V _{DC} Main power supply +5V stand-by
Networking	2x NBase-T Ethernet interfaces, supporting 2.5Gb Ethernet connection, managed by as many Intel® i225 2.5GbE Controllers Optional on-board M.2 1216 module, supporting WiFi 802.11ax (WiFi 6E) MIMO 2x2 + MU-MIMO and Bluetooth 5.2, external antennas* *Certification upon request	Operating System	Windows 10 IoT Enterprise LTSC Windows Server 2022 Wind River VxWorks 7.0 Linux Kernel LTS (Ubuntu) Wind River Linux Yocto Android
USB	Up to 4 x USB 4.0 / USB 3.2 Host ports 4 x USB 2.0 Host port	Operating Temperature*	-40°C ÷ +85°C (Industrial)
		Dimensions	120 x 95 mm (COM-HPC® Size A Form factor, Client pinout)

*Measured at any point of SECO standard heatspreader for this product, during any and all times (including start-up). Actual temperature will widely depend on application, enclosure and/or environment. Upon customer to consider application-specific cooling solutions for the final system to keep the heatspreader temperature in the range indicated.

SOM-COM-HPC-A-RPL

COM HPC® Client module Size A, with 13th Gen Intel® Core™ processors (Codename: Raptor Lake – H/P/U series)

BLOCK DIAGRAM

